



## Introduction

ARC-10 is a low cost, DIN rail mounting controller unit for alarm annunciation and remote control using SMS. The unit incorporates a GSM/GPRS modem, 2 digital inputs, 2 power relay outputs and a serial RS-232 port.

Up to five hundred users can be configured to switch a relay output with a toll-free phone call (e.g. for opening the garage door or a parking barrier). Ten users can be configured as alarm recipients in case of an alarm situation.

## Simple setup and operation

All setup and control is done using your mobile phone. Simple ASCII configuration commands are used for unit setup and control. Several commands can be packed in one SMS. The RS-232 interface can be used to alternatively setup and test the unit using a PC or an ASCII terminal. The rich command set features commands for configuring input alarm parameters, defining users and controlling system outputs with time related parameters. Dedicated Smartphone Applications are available for Android and iOS (iPhone).

## **Technical characteristics**

Power supply 12...24 VDC +/-10%, 30...200mA max

Modem Quad Band 2G or 4GLTE

RF Connector SMA

Digital inputs 2, 12..30VDC

Digital outputs 2, Relais 250V/8A (AC1)
Serial port RS232C, bis 921 kBit/s

Dimensions 71 x 90 x 58mm

Command set Over 40 ASCII commands

## Accessories

PS-3B-S 230V/12VDC, 0.8A power supply SCCM-09-MF Serial cable

T-AT559 Quad Band GSM Antenna (SMA) T-AT659 Mutliband LTE Antenna (SMA)

RoHS Compliant
Directive 2002/95/EC



Infinite Informatics, Ltd.

1, Valaoritou Street 54626, Thessaloniki, Greece

T: +30 2310 553545, F: +30 2310 552006

E: info@indinf.gr

W: www.infinite.com.gr, www.indinf.gr

Representative - authorized dealer